

Panelboard and Switchboard Accessories - Component

COMPANY

GUND CO INC

2121 WALTON RD
SAINT LOUIS, MO 63114-5807 United States

E354884

Marking: Company name or trademark  ,  , and model designation.

Note: For additional marking information, refer to the [Guide Information Page](#).

Standoff insulators for support of live parts only, Model(s): GINS 2015-2C Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for support of live parts only, Model(s): GINS 2165-1A Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for support of live parts only, Model(s): GINS 2165-1B Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for support of live parts only, Model(s): GINS 2165-3A Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for support of live parts only, Model(s): GINS 2165-3B Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for support of live parts only, Model(s): GINS 2165-5A Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for support of live parts only, Model(s): GINS 2165-M1A Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for support of live parts only, Model(s): GINS 2165-M1B Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1461-1A Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1461-1B Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1461-1C Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1461-2C Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1461-3A Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1461-4A Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1461-5A Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1461-M1A+ Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1461-M1B Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1461-M1C Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1461-M2C Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1603-2A Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1603-2D Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1603-M2A Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1603-M2D Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872 -1F Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-1A Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-1B Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-1C Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-1D Cat. No. and suffix numbers may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-1E Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-2A Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-2B Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-2C Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-2D Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-2E Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-3E Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-3F Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-M1A Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-M1B Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-M1C Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-M1D Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-M1E Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-M1F Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-M2A Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-M2B Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-M2C Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-M2D Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-M2E Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-M3E Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 1872-M3F Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2015-1A Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2015-2A Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2015-2B Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2015-3A Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2015-3B Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2015-3C Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2015-3D Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2015-4C Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2015-4D Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2015-M1A Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2015-M2A Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2015-M2B Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2015-M2C Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2015-M3A Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2015-M3B Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2015-M3C Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2015-M3D Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2015-M4C Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2015-M4D Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2017-2A Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2017-2C Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2017-3A Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2017-3A-B Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2017-3C Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2017-4C Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2017-M2 Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2017-M2A Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2017-M3C Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 2035-1A Cat. No. and/or suffixes may be followed by -B or -S, suitable only for sole support of life parts.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061 GINS 3061-1A+, GINS 3061-1B+, GINS 3061-2B+, GINS 3061-3A+, GINS 3061-3B+, GINS 3061-3C+, GINS 3061-3D+, GINS 3061-3E+, GINS 3061-3F+, GINS 3061-3G+, GINS 3061-3H+, GINS 3061-4C+, GINS 3061-4D+, GINS 3061-4F+, GINS 3061-5F+, GINS 3061-M1A+, GINS 3061-M1B+, GINS 3061-M2B+, GINS 3061-M3A+, GINS 3061-M3B+, GINS 3061-M3C+, GINS 3061-M3D+, GINS 3061-M3E+, GINS 3061-M3F+, GINS 3061-M3G+, GINS 3061-M3H+, GINS 3061-M4C+, GINS 3061-M4D+, GINS 3061-M4F+, GINS 3061-M5F+, GINS 3061-6A+, GINS 3061-M6A+

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-1A Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-1B Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-2B Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-3A Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-3B Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-3C Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-3D Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-3E Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-3F Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-3G Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-3H Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-4C Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-4D Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-4F Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-5F Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-M1A Cat. No. and/or suffixes may be followed by -B or -S.
Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-M1B Cat. No. and/or suffixes may be followed by -B or -S.
Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-M2B Cat. No. and/or suffixes may be followed by -B or -S.
Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-M3A Cat. No. and/or suffixes may be followed by -B or -S.
Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-M3B Cat. No. and/or suffixes may be followed by -B or -S.
Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-M3C Cat. No. and/or suffixes may be followed by -B or -S.
Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-M3D Cat. No. and/or suffixes may be followed by -B or -S.
Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-M3E Cat. No. and/or suffixes may be followed by -B or -S.
Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-M3F Cat. No. and/or suffixes may be followed by -B or -S.
Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-M3G Cat. No. and/or suffixes may be followed by -B or -S.
Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-M3H Cat. No. and/or suffixes may be followed by -B or -S.
Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-M4C Cat. No. and/or suffixes may be followed by -B or -S.
Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-M4D Cat. No. and/or suffixes may be followed by -B or -S.
Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-M4F Cat. No. and/or suffixes may be followed by -B or -S.
Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 3061-M5F Cat. No. and/or suffixes may be followed by -B or -S.
Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 4610-15 Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 4610-81 Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 4610-M15 Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 4610-M81 Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 4640-15 Cat. No. and/or suffixes may be followed by -B or -S.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 4640-81 Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 4640-M15 Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Standoff insulators for use with UL891 Annex G, Model(s): GINS 4640-M81 Cat. No. and/or suffixes may be followed by -B or -S. Cat. Nos. with M suffix are with equivalent metric dimensions.

Last Updated on 2025-03-13

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."